



## CLEANING PRODUCTS FOR AEROSPACE & DEFENSE AEROSPACE APPROVAL LIST

COMPANY	Solvents <sup>1</sup>										Aqueous	Vapor Degreasing			Wax Masking
	AXAREL®							BIOACT®		RE-ENTRY®	CleanSafe™	LENIUM®			AEROWAX™
	56	1000	2000	3000	4000	4100	6100	9100	105	280/280E	Prepsolv	787C	ES/GS/XS	FHD	IPS
Airbus		.	.	.	.					.					
Bell Helicopter							.	.			.	.			
Boeing Company	.	.	.	.						.	.	.2			NR
Boeing Rotocraft Systems											.2				
Bombardier							.	.							
CFM								.	.		.				
Engine Alliance											.2				
GE Aviation	.							.	.		.				
Goodrich Actuation Systems						.	.								
Goodrich Landing Gear												.			
Goodrich Power Systems								.					.	.	
Goodrich Wheels & Brakes			.	.											
GulfStream Aerospace								.							
International Aero Engines								.	.		.				
Honeywell Aerospace		.	.	.	.			.	.		.				
Lockheed Martin		.	.	.	.			.				.			
Messier-Dowty	.										.				
Messier-Bugatti			.	.											
Department of Defense		.	.	.	.										
Pratt & Whitney		.	.	.				.	.		.				.
Praxair												.			
Rolls-Royce						.	.	.	.		.		.		NR
Sikorsky Aircraft		.2													
Scott Aviation												.			
Spirit AeroSystems											.				
Turbomeca											.	.2			
United Services								.			.				
Vought Aircraft											.2				

1 – Includes blended solvents, bio-based cleaners, semi-aqueous cleaners and manual cleaners    2 - Approval Pending    NR – Not Required

AXAREL, BIOACT, LENIUM and RE-ENTRY are registered trademarks of Vantage Specialty Chemicals Inc.  
AEROWAX and CleanSafe are trademarks of Vantage Specialty Chemicals Inc.

Date 11/28/2011

Petroferm Inc. • 3938 Porett Dr. • Gurnee, IL 60031 • (847) 244-3410 • aerospace@petroferm.com • www.petroferm.com

Products	Approvals/Test Method Conformance
<p><b>AEROWAX™ MT</b></p> <p><b>Type:</b> Microcrystalline Masking Wax</p> <p><b>Application:</b> Immersion</p>	<ul style="list-style-type: none"> <li>• Approved by <b>Pratt &amp; Whitney</b> as PMC 9551 Masking Wax Compound</li> <li>• ASTM F945, Hot Corrosion (per PWA 36604 Rev D)</li> </ul>
<p><b>AXAREL® 56</b></p> <p><b>Type:</b> Semi-Aqueous</p> <p><b>Application:</b> Immersion Spray</p>	<ul style="list-style-type: none"> <li>• Approved by <b>Boeing</b> as PSD 6-3 for BAC 5200 Cleaning, Preserving &amp; Re-lubricating Anti-friction Bearings, Method II A Pressure Spray Cleaning</li> <li>• Approved by <b>Boeing</b> BAC 5763 Type II Emulsion Cleaning &amp; Aqueous Degreasing (5-25% in Spray; 5-100% in immersion)</li> <li>• Approved by <b>GE Aviation</b> per the Master Cleaner List 3.6.5 identified in GE Aviation SCWC (supply chain web center). Aqueous Immersion Cleaners and Water-Based Spray Cleaners (25%)</li> <li>• Supported by <b>Hawker Pacific Aerospace, UK, Ltd.</b> as a Diphasic Cleaning/Degreasing Chemical</li> <li>• Approved by <b>Messier-Dowty</b> PCS-2620 for use on all materials and coatings on Messier-Dowty parts (Memo LMP 09/031)</li> <li>• ASTM F519</li> </ul>
<p><b>AXAREL® 1000</b></p> <p><b>Type:</b> Solvent</p> <p><b>Application:</b> Manual Cleaning Immersion Airless Vacuum</p>	<ul style="list-style-type: none"> <li>• Approved under <b>MIL-PRF-680B</b> Degreasing Solvent Type I Low Flash Point (Military Symbol SD-1) (DS-0020)</li> <li>• Approved by <b>Airbus</b> per Consumable Materials List (CML) (ref. MIL-PRF-680)</li> <li>• Approved by <b>Airbus</b> per A330 Maintenance Manual Item 11-002 Dry Cleaning Solvent (ref. MIL-PRF-680)</li> <li>• Approved by <b>Boeing</b> as PSD 6-88 for BAC 5750 Solvent Cleaning (as optional to P-D-680 specification)</li> <li>• Approved by <b>Honeywell Aerospace</b> per MIL-PRF-680B qualifications</li> <li>• Approved by <b>Lockheed Martin</b> STP57-201, Rev. H Cleaning of Carbon &amp; Low Alloy Steels (EPS G41.14) (<i>MIL-PRF-680B supersedes P-D-680</i>)</li> <li>• Approved by <b>Pratt &amp; Whitney</b> as PMC 9001-1, -2, -7, -10 Stoddard Solvent (MIL-PRF-680, Type I, II or III)</li> <li>• ASTM D1353, D1296, D130, F1110, F483, F945</li> <li>• NSN# 6850-01-474-2302, 6850-01-474-2309, 6850-01-474-2313, 6850-00-264-9039</li> </ul>



CLEANING PRODUCTS FOR AEROSPACE & DEFENSE  
**AEROSPACE APPROVAL LIST**

Products	Approvals/Test Method Conformance
<p><b>AXAREL® 2000</b></p> <p><b>Type:</b> Solvent</p> <p><b>Application:</b> Manual Cleaning Immersion Airless Vacuum</p>	<ul style="list-style-type: none"> <li>• Approved under <b>MIL-PRF-680B</b> Degreasing Solvent Type II High Flash Point (Military Symbol SD-2) (DS-0018)</li> <li>• Approved by <b>Airbus</b> per Consumable Materials List (CML) (ref. MIL-PRF-680)</li> <li>• Approved by <b>Airbus</b> per A330 Maintenance Manual Item 11-002 Dry Cleaning Solvent (ref. MIL-PRF-680)</li> <li>• Approved by <b>Boeing</b> as PSD 6-88 for BAC 5750 Solvent Cleaning (as optional to P-D-680 specification)</li> <li>• Approved by <b>Goodrich Wheels and Brakes</b> Component Maintenance Manual 2-1577 Series (Task 32-41-81-100-801-A01) per MIL-PRF-680</li> <li>• Approved by <b>Honeywell Aerospace</b> per MIL-PRF-680B qualifications</li> <li>• Approved by <b>Lockheed Martin</b> STP57-201, Rev. H Cleaning of Carbon &amp; Low Alloy Steels (EPS G41.14) (<i>MIL-PRF-680B supersedes P-D-680</i>)</li> <li>• Approved by <b>Messier-Bugatti</b> Component Maintenance Manual 2-1577 Series (Task 32-41-81-100-801-A01) per MIL-PRF-680</li> <li>• Approved by <b>Pratt &amp; Whitney</b> as PMC 9001-3, -4, -8 Stoddard Solvent (MIL-PRF-680, Type I, II or III)</li> <li>• ASTM D1353, D1296, D130, F1110, F483, F945</li> <li>• NSN# 6850-01-474-2319, 6850-01-474-2317, 6850-01-474-2316, 6850-00-637-6135</li> </ul>
<p><b>AXAREL® 3000</b></p> <p><b>Type:</b> Solvent</p> <p><b>Application:</b> Manual Cleaning Immersion Airless Vacuum</p>	<ul style="list-style-type: none"> <li>• Approved under <b>MIL-PRF-680B</b> Degreasing Solvent Type III Very High Flash Point (200°F) (Military Symbol SD-3) (DS-0017)</li> <li>• Approved by <b>Airbus</b> per Consumable Materials List (CML) (ref. MIL-PRF-680)</li> <li>• Approved by <b>Airbus</b> per A330 Maintenance Manual Item 11-002 Dry Cleaning Solvent (ref. MIL-PRF-680)</li> <li>• Approved by <b>Boeing</b> as PSD 6-88 for BAC 5750 Solvent Cleaning (as option to P-D-680 specification)</li> <li>• Approved by <b>Goodrich Wheels and Brakes</b> Component Maintenance Manual 2-1577 Series (Task 32-41-81-100-801-A01) per MIL-PRF-680</li> <li>• Approved by <b>Honeywell Aerospace</b> per MIL-PRF-680B qualifications</li> <li>• Approved by <b>Lockheed Martin</b> STP57-201, Rev. H Cleaning of Carbon &amp; Low Alloy Steels (EPS G41.14) (<i>MIL-PRF-680B supersedes P-D-680</i>)</li> <li>• Approved by <b>Messier-Bugatti</b> Component Maintenance Manual 2-1577 Series (Task 32-41-81-100-801-A01) per MIL-PRF-680</li> <li>• Approved by <b>Pratt &amp; Whitney</b> as PMC 9001-5, -6, -9 Stoddard Solvent (MIL-PRF-680, Type I, II or III)</li> <li>• ASTM D1353, D1296, D130, F1110, F483, F945</li> <li>• NSN# 6850-01-474-2318, 6850-01-474-2320, 6850-01-474-2321</li> </ul>

AXAREL, BIOACT, LENIUM and RE-ENTRY are registered trademarks of Vantage Specialty Chemicals Inc.  
 AEROWAX and CleanSafe are trademarks of Vantage Specialty Chemicals Inc.

Date 11/28/2011

Petroferm Inc. • 3938 Porett Dr. • Gurnee, IL 60031 • (847) 244-3410 • aerospace@petroferm.com • www.petroferm.com

Products	Approvals/Test Method Conformance
<p><b>AXAREL® 4000</b></p> <p><b>Type:</b> Solvent</p> <p><b>Application:</b> Manual Cleaning Immersion Airless Vacuum</p>	<ul style="list-style-type: none"> <li>• Approved under <b>MIL-PRF-680B</b> Degreasing Solvent Type IV High Flash Point with Citrus Odor (Military Symbol SD-4) (DS-0023)</li> <li>• Approved by <b>Airbus</b> per Consumable Materials List (CML) (ref. MIL-PRF-680)</li> <li>• Approved by <b>Airbus</b> per A330 Maintenance Manual Item 11-002 Dry Cleaning Solvent (ref. MIL-PRF-680)</li> <li>• Approved by <b>Honeywell Aerospace</b> per MIL-PRF-680B qualifications</li> <li>• Approved by <b>Lockheed Martin</b> STP57-201, Rev. H Cleaning of Carbon &amp; Low Alloy Steels (EPS G41.14) (<i>MIL-PRF-680B supersedes P-D-680</i>)</li> <li>• ASTM D1353, D130, F1110, F483, F945</li> <li>• NSN# 6850-01-472-2722, 6850-01-472-2717, 6850-01-472-2719</li> </ul>
<p><b>AXAREL® 4100</b></p> <p><b>Type:</b> Solvent</p> <p><b>Application:</b> Manual Cleaning Immersion</p>	<ul style="list-style-type: none"> <li>• Approved by <b>Goodrich Actuation Systems</b> 981-100-020 Issue 4 Solvent Degreasing</li> <li>• Approved by <b>Rolls-Royce</b> CSS No. 255 Type A Non-Halogenated Organic Solvent Cleaner (MLC104)</li> <li>• Approved by <b>Rolls-Royce</b> OMat 1/257M Solvent Cleaner</li> <li>• SAE ARP 1755B, ASTM F945</li> <li>• NSN# 8010-01-535-0740</li> </ul>
<p><b>AXAREL® 6100</b></p> <p><b>Type:</b> Solvent</p> <p><b>Application:</b> Manual Cleaning Immersion</p>	<ul style="list-style-type: none"> <li>• Approved by <b>Bell Helicopter</b>, Bulletin No 1915, Solvents, Blended Organic, Cold Degreasing</li> <li>• Approved by <b>Goodrich Actuation Systems</b> 981-100-020 Issue 4 Solvent Degreasing</li> <li>• Approved by <b>Rolls-Royce</b> CSS No 255 Type A Non-Halogenated Organic Solvent Cleaner (MLC104)</li> <li>• Conforms to <b>Pratt &amp; Whitney</b> Hot Corrosion Testing of Standard Gas Turbine Engine Alloys (AMS 4037, 4375, 6359, 5508, 5536, 5544, 5608)</li> <li>• SAE ARP 1755B, ASTM F945 (20% &amp; 100%)</li> </ul>

Products	Approvals/Test Method Conformance
<p><b>AXAREL® 9100</b></p> <p><b>Type:</b> Solvent</p> <p><b>Application:</b> Manual Cleaning Immersion</p>	<ul style="list-style-type: none"> <li>• Conforms to <b>Boeing</b> D6-17487 Rev M Exterior &amp; General Cleaners &amp; Liquid Waxes</li> <li>• Approved by <b>Bombardier</b> Service Bulletin S.B. 670BA-34-027 Cleaning Pitot and Static Lines and Fittings, Sec 3.B. (CRJ: CL-600-2C10,-2D24)</li> <li>• Approved by <b>Goodrich Power Systems</b> for Co-Solvent Vapor Degreasing (with LENIUM IPS). Process Specification No: 914-014-078 to 085. Title: Solvent and Aqueous Degreasing and Cleaning. Issue: 9</li> <li>• Conforms to <b>MIL-PRF-680B</b> Degreasing Solvent Type III Very High Flash Point (200°F) (Military Symbol SD-3)</li> <li>• Approved by <b>Rolls-Royce</b> CSS No. 255 Type A Non-Halogenated Organic Solvent Cleaner (MLC104)</li> <li>• Approved by <b>Rolls-Royce</b> OMat 1/257M Solvent Cleaner</li> <li>• Conforms to <b>Royal Air Force Harrogate</b> Montreal Protocol Alternatives Programme Replacement for ODPs ('95)</li> <li>• ASTM D1353, D1296, D130, F1110, F483, F945, SAE ARP 1755A</li> </ul>
<p><b>BIOACT® 105</b></p> <p><b>Type:</b> Solvent</p> <p><b>Application:</b> Manual Cleaning Immersion</p>	<ul style="list-style-type: none"> <li>• Approved by <b>Bell Helicopter</b> Bulletin No: 1915 Solvents, Blended Organic, Cold Degreasing (Liquid &amp; Pre-Saturated Wipes)</li> <li>• Conforms to <b>Boeing</b> D6-17487 Rev L Exterior &amp; General Cleaners &amp; Liquid Waxes (exceptions: ASTM F-484 Stress Cracking)</li> <li>• Approved by <b>Bombardier</b> per BAPS 180-009 as a General (G) Manual Solvent Cleaner.</li> <li>• Approved by <b>CFM</b> CP# 2719 Rev 76</li> <li>• Conforms to <b>Douglas Aircraft Co</b> CSD #1 General Purpose Cleaner (exceptions: ASTM F-484 Stress Cracking)</li> <li>• Approved by <b>GE</b> for Cleaning Method No 23 Hand-Wipe Degreasing, SPM Task 70-21-23-110-053 (CO4-251)</li> <li>• Approved by <b>GE</b> for as alternate to SPM TASK 70-21-01-110-001 Cleaning Method No 1 Solvent Degreasing</li> <li>• Approved by <b>GE</b> for as alternate to SPM TASK 70-21-22-110-042 Cleaning Method No 22 Light Duty Aqueous Cleaning for Localized Hand-Wipe Cleaning</li> <li>• Approved by <b>GulfStream Aerospace</b> Standard GAS115H for Solvent Cleaner/Degreaser, Mixed Hydrocarbons, Part# GAS115H1</li> <li>• Approved by <b>Honeywell</b> C5049 Cleaning of Titanium &amp; Titanium Alloys</li> <li>• Approved by <b>International Aero Engines (IAE)</b> CoMat 01-506 (Liquid), CoMat 01-506A (Pre-saturated Wipes)</li> <li>• Approved by <b>Pratt &amp; Whitney</b> as PMC 8929 Hand Wiping Solvent for SPOP 209 Degreasing of Parts by Solvent Wiping (SPM Rev 120, Part# 585005)</li> <li>• Approved by <b>Pratt &amp; Whitney</b> as PMC 8929 Hand Wiping solvent for POP 1800-U Masking of Parts Prior to Selective Painting, Chemical Processing, Painting or Stripping</li> <li>• Conforms to <b>Pratt &amp; Whitney</b> PWA 36604 Rev D Hot Corrosion (AMS 4037)</li> <li>• Approved by <b>Rolls-Royce</b> CSS No 255 Type A Non-Halogenated Organic Solvent Cleaner (MLC104)</li> <li>• Approved by <b>Rolls-Royce</b> OMat 1/257S Solvent Cleaner</li> </ul>

Products	Approvals/Test Method Conformance
<b>BIOACT® 105</b> <i>continued</i>	<ul style="list-style-type: none"> <li>Approved by <b>United Airlines</b> Engine Parts Cleaning, Part #: SOL3001-17 for BIOACT 105 Precision Cleaner, SOL3001-17TWL10X12 for Saturated Wipes</li> <li>ASTM F945, F1110, F502, F519, F485, F483, F2111, D3941, D2879, D1901, D1613, B117, G46</li> </ul>
<b>BIOACT® 121</b>  <b>Type:</b> Solvent  <b>Application:</b> Manual Cleaning Immersion	<ul style="list-style-type: none"> <li>Conforms to <b>Airbus</b> per A330 Maintenance Manual Item 11-016 Cleaning Solvent (ref. BAC 5750)</li> <li>Conforms to <b>Boeing</b> per BAC 5750 Solvent Cleaning Sec. 5.11: d-Limonene, 95% minimum</li> <li>Conforms to <b>Boeing</b> D6-17487 Rev N Solvent Cleaners, General Cleaning</li> <li>Conforms to <b>Boeing</b> D6-17487 Rev L Exterior and General Cleaners and Liquid Waxes</li> <li>Conforms to <b>Douglas Aircraft Company</b> CSD #1 Type 1 Materials &amp; Procedures for General Exterior Cleaning of Painted &amp; Unpainted Surfaces</li> <li>ASTM F1110, F502, F519, F945, F485, F484, F483</li> </ul>
<b>BIOACT® 145</b>  <b>Type:</b> Solvent  <b>Application:</b> Manual Cleaning Immersion	<ul style="list-style-type: none"> <li>Conforms to <b>Boeing</b> D6-17487 Rev. L Exterior &amp; General Cleaners &amp; Liquid Waxes</li> <li>Conforms to <b>Douglas Aircraft Company</b> CSD #1 General Purpose Cleaner</li> <li>Approved by <b>GulfStream Aerospace</b> Standard GAS115H for Solvent Cleaner/Degreaser, Mixed Hydrocarbons, Part# GAS115H1</li> <li>ASTM F945, F1110, F502, F519, F485, F483</li> </ul>

Products	Approvals/Test Method Conformance
<p><b>BIOACT® 280</b></p> <p><b>Type:</b> Semi-Aqueous</p> <p><b>Application:</b> Immersion</p>	<ul style="list-style-type: none"> <li>• Approved by <b>GE Aviation</b> as a general parts cleaner and as a plating wax remover on GEAE and CFMI engine hardware.</li> <li>• Approved by <b>GE Aviation</b> per the Master Cleaner List 3.6.5 identified in GE Aviation SCWC (supply chain web center). Semi-Aqueous Immersion Cleaners (100%)</li> <li>• Approved by <b>Honeywell</b> Process Specification C7010, Rev H for dewaxing and general cleaning of mechanical hardware</li> <li>• Conforms to <b>Honeywell</b> EMS 53170 Rev C 10-21-97 Type 1 Material Requirements for Aqueous Cleaning and Semi-Aqueous Degreasing, Tests A,B,C,F,G</li> <li>• Supported by <b>Hawker Pacific Aerospace, UK.</b> as a General Purpose High Temperature Degreasing Agent</li> <li>• Approved by <b>International Aero Engines (IAE)</b> CoMat 01-460</li> <li>• Approved by <b>Pratt &amp; Whitney</b> MCL E-205 Titanium Stress Corrosion Test</li> <li>• Approved by <b>Pratt &amp; Whitney</b> as PMC 8913-1,-2 Wax Removal Solvent for SPOP 37 Method 2 Removal of Plating Wax (SPM Rev 120, Part #585005)</li> <li>• Approved by <b>Pratt &amp; Whitney</b> as PMC 8913-1,-2 Wax Removal Solvent for POP 1800-U Masking of Parts Prior to Selective Painting, Chemical Processing, Painting or Stripping</li> <li>• ASTM F1110, F2111, F945, F519</li> </ul>
<p><b>BIOACT® 280E</b></p> <p><b>Type:</b> Semi-Aqueous</p> <p><b>Application:</b> Immersion</p>	<ul style="list-style-type: none"> <li>• Conforms to <b>Boeing</b> D6-17487 Rev N Exterior and General Cleaners and Liquid Waxes, Polishes and Polishing Compounds (exceptions: ASTM F-484 Stress Cracking Tests on Acrylics, Type C</li> <li>• Approved by <b>CFM</b> CP# 2720 Rev 76</li> <li>• Approved by <b>GE Aviation</b> 70-80-04 Solvent, Wax Removal (C04-287)</li> <li>• Approved by <b>GE Aviation</b> per the Master Cleaner List 3.6.5 identified in GE Aviation SCWC (supply chain web center). Semi-Aqueous Immersion Cleaners (100%)</li> <li>• Approved by <b>International Aero Engines (IAE)</b> CoMat 01-460</li> <li>• Conforms to <b>Pratt &amp; Whitney</b> PWA 36604 Rev B Hot Corrosion Testing of Standard Gas Turbine Engine Alloys</li> <li>• Approved by <b>Pratt &amp; Whitney</b> as PMC 8913-11,-12 Wax Removal Solvent for SPOP 37 Method 2 Removal of Plating Wax (SPM Rev 120, Part #585005)</li> <li>• Approved by <b>Pratt &amp; Whitney</b> as PMC 8913-11,-12 Wax Removal Solvent for POP 1800-U Masking of Parts Prior to Selective Painting, Chemical Processing, Painting or Stripping</li> <li>• Approved by <b>Rolls-Royce</b> OMat 1/288D Wax Remover</li> <li>• Approved by <b>Rolls-Royce</b> CSS No 254 Class A Semi-Aqueous Cleaning Fluids Suitable for Use on Metallic Materials as CM0000044 - Class A: BIOACT 280 (MLC104/1)</li> <li>• ASTM F945, F502, F519-93, F1110, F2111, SAE ARP 1755B</li> </ul>

Products	Approvals/Test Method Conformance
<p><b>CleanSafe™ 787C</b></p> <p><b>Type:</b> Aqueous</p> <p><b>Application:</b> Immersion Spray Ultrasonics</p>	<ul style="list-style-type: none"> <li>• Approved by <b>Bell Helicopter</b> as material code M/C 2100-00097</li> <li>• Approved by <b>Boeing</b> as PSD 6-57 for BAC 5763 Type II Grade A Emulsion Cleaning &amp; Aqueous Degreasing</li> <li>• Approved by <b>Boeing</b> as PSD 6-153 for BAC 5749 Alkaline Cleaning</li> <li>• Approval pending by <b>Boeing Rotocraft Systems</b></li> <li>• Approved by <b>CFM</b> as CP2735 for CFM SPM 70-21-18 Light Duty Aqueous Cleaning, Immersion Method 2 (Rev 78)</li> <li>• Approval by <b>CFM</b> as CP2735 for CFM SPM 70-21-19 Light Duty Aqueous cleaning Spray Method (Rev 79)</li> <li>• Approved by <b>Engine Alliance LLC</b> to GP7000 SPM EAP-2202, Aqueous Cleaner, Immersion Cleaning (in next revision)</li> <li>• Conforms to <b>GE Aviation</b> Appendix F Recommended Practice for Certifying Agent Approval of Cleaning Products Used on Metallic Jet Engine Hardware (Sec. 3.1.1, -4, -5, -6, --9, -10, -12)</li> <li>• Approved by <b>GE Aviation</b> as C04-289 Cleaner, Mild Alkaline listed in GE SPM 70-21-22 Light Duty Aqueous Cleaning (S1207 – Light Duty Alkaline Cleaner – C04-289)</li> <li>• Approved by <b>Honeywell</b> for C5012 Aqueous Cleaning in accordance to EMS 53170 Material Requirements for Aqueous and Semi-Aqueous Degreasing (Type I and Type II Cleaner)</li> <li>• Approved by <b>International Aero Engines (IAE)</b> CoMat 01-565</li> <li>• Approved by <b>Messier-Dowty</b> PCS-2621 for use on all materials and coatings on Messier-Dowty parts (Memo LMP 09/031)</li> <li>• Conforms to <b>MIL-PRF-87937D</b> Cleaning Compound, Aerospace Equipment Type IV – Heavy Duty, Water-Dilutable Cleaning Compound</li> <li>• Approved by <b>Pratt &amp; Whitney</b> as SPMC 190 referenced by SPS 190 Immersion Cleaning for SPOP 209 Degreasing of Parts by Aqueous Cleaning</li> <li>• Approved by <b>Pratt &amp; Whitney</b> as PMC 1465 referenced by PS 437 Alkali Cleaner (Immersion) for POP 1800-U Masking of Parts Prior to Selective Painting, Chemical Processing, Painting or Stripping</li> <li>• Approved by <b>Pratt &amp; Whitney</b> as PMC 1465 referenced by PS 437 Alkali Cleaner (Immersion) for POP 573-AD Alkali Cleaning (Immersion)</li> <li>• Approved by <b>Pratt &amp; Whitney</b> as PMC 1465 referenced by PS 436 Alkali Cleaner (Spray Wash) for POP 581-R Alkali Cleaning in Cabinet-Type Automatic Spray Wash Equipment</li> <li>• Conforms to <b>Pratt &amp; Whitney</b> PWA 36604 Revision D</li> <li>• Approved by <b>Rolls-Royce</b> CSS204 Aqueous Cleaners (MLC104 ISSUE 18 - APRIL 2009)</li> <li>• Approved by <b>Rolls-Royce</b> OMat 1/24AL Aqueous Cleaner</li> <li>• Approved by the <b>SCAQMD</b> as a Clean Air Solvent</li> <li>• Approved by <b>Spirit AeroSystems</b> as SPS 107630 Emulsion Cleaning &amp; Aqueous Degreasing</li> <li>• Approved by <b>United Services</b> (United Airlines) CLE3007-34</li> </ul>

Products	Approvals/Test Method Conformance
<b>CleanSafe™ 787C</b> <i>continued</i>	<ul style="list-style-type: none"> <li>• ASTM F519, F483, D816, F945, F1111, F1110, F502, E1447, Wet Adhesion Tape Test, MIL-DTL-83488d, SAE ARP 1755B, (Chem. Analysis, Cleaning Ability, Etch Rate, Cleaning Prior to FPI – per EMS53170)</li> </ul>
<b>LENIUM® ES</b>  <b>Type:</b> nPB-based  <b>Application:</b> Vapor Degreasing	<ul style="list-style-type: none"> <li>• Approved by <b>Goodrich Landing</b> LGPS 1400 Solvent Cleaning/Degreasing</li> <li>• Approved by <b>Lockheed Martin</b> EMAP G41.149</li> </ul>
<b>LENIUM® GS</b>  <b>Type:</b> nPB-based  <b>Application:</b> Vapor Degreasing	<ul style="list-style-type: none"> <li>• Approved by <b>Bell Helicopter</b> Bulletin No.: 1918 n-Propyl Bromide, Vapor Degreasing Grade</li> <li>• Approved by <b>Praxair</b> ID# GDE 10055434</li> <li>• Approved by <b>Scott Aviation</b> SMP No.: 7700009 Rev AP, Cleaning of Components &amp; Assemblies For Use in Breathing Equipment</li> <li>• ASTM F519, F1110, F945</li> </ul>
<b>LENIUM® XS</b>  <b>Type:</b> nPB-based  <b>Application:</b> Vapor Degreasing	<ul style="list-style-type: none"> <li>• Conforms to <b>Boeing</b> D6-17487 Rev P Solvent Cleaners/General Cleaning</li> <li>• Conforms to <b>Douglas</b> CSD #1 Type 1 General Purpose Cleaner (exceptions: Stress Cracking Test on Acrylics)</li> <li>• Approved by <b>Lockheed Martin</b> EMAP G41.149</li> <li>• ASTM F519, F1110, F502, F945, F485, F483, SAE ARP 1755B</li> </ul>
<b>LENIUM® FHD</b>  <b>Type:</b> HFC-based  <b>Application:</b> Vapor Degreasing	<ul style="list-style-type: none"> <li>• Conforms to <b>Boeing</b> D6-17487 Rev P Solvent Cleaners/General Cleaning</li> <li>• Conforms to <b>Douglas</b> CSD #1 Type 1 General Purpose Cleaner (exceptions: Stress Cracking Test on Acrylics)</li> <li>• Approved by <b>Goodrich Power Systems</b> for Mono-Solvent Vapor Degreasing. Process Specification No: 914-014-078 to 085. Title: Solvent and Aqueous Degreasing and Cleaning. Issue: 9</li> <li>• Approved by <b>Rolls-Royce</b> OMat 1/21E Vapor Degreasing</li> <li>• ASTM F519, F1110, F502, F945, F485, F483, SAE ARP 1755B</li> </ul>

Products	Approvals/Test Method Conformance
<p><b>LENIUM<sup>®</sup> IPS</b></p> <p><b>Type:</b> HFC-based</p> <p><b>Application:</b> Vapor Degreasing</p>	<ul style="list-style-type: none"> <li>Approved by <b>Goodrich Power Systems</b> for Co-Solvent Vapor Degreasing (with AXAREL 9100). Process Specification No: 914-014-078 to 085. Title: Solvent and Aqueous Degreasing and Cleaning. Issue: 9</li> </ul>
<p><b>RE-ENTRY<sup>®</sup> Prepsolv</b></p> <p><b>Type:</b> Solvent</p> <p><b>Application:</b> Manual Cleaning Immersion</p>	<ul style="list-style-type: none"> <li>Approved by <b>Boeing</b> BAC 5750 Solvent Cleaning Revision M (released April 22, 2011)</li> </ul>